

DYROS 30

Brass connectors with 6 mm passage capacity* for water, grease, air, oil etc.

- developed specifically for coolants in plastic tools

Today Dyros 30 can be found everywhere:

- on plastic moulds
- on compressed-air plants
- on oxygen and gas cylinders
- in operating rooms
- and in numerous other places

In short, Dyros can be found wherever small dimensions, reliability and safety are a must.

All connectors have built-in valves that are perfectly tight even at very low pressure.

A locking device is automatically released upon engagement, so that the connector can be operated by one hand.

Safety connectors with hose fitting

				3/8" (9,5 ⁰)	1/2" (12,7 ⁰)		
Straight				Art. No. SLK 316	Art. No. SLK 318		
		90°			Art. No. SVK 316/90		
		45°			Art. No. SVK 316/45		

Safety connectors with internal thread

		BSP1/4"	BSP3/8"	M14x1.5	M16x1.5
Straight		Art. No. SLKR 314 (HEX = 17)	Art. No. SLKR 338 (HEX = 20)	Art. No. SLKM 345 (HEX = 17)	Art. No. SLKM 365 (HEX = 20)

Safety connectors with external thread

		BSP1/4"	BSP3/8"	M14x1.5	M16x1.5	
Straight		Art. No. SLKUR 314 (HEX = 17)	Art. No. SLKUR 338 (HEX = 17)	Art. No. SLKUM 345 (HEX = 17)	Art. No. SLKUM 365 (HEX = 17)	
		90°	Art. No. SVKUR 314/90	Art. No. SVKUR 338/90	Art. No. SVKUM 345/90	Art. No. SVKUM 365/90
		45°	Art. No. SVKUR 314/45	Art. No. SVKUR 338/45	Art. No. SVKUM 345/45	Art. No. SVKUM 365/45

Safety adaptor connector with nipple fitting

		serie:	6	40	90
Straight			Art. No. SLK 300/600	Art. No. SLK 300/400	Art. No. SLK 300/900

Dyros products are unimpeachable quality - down to the smallest detail

The Thread BSP corresponds to G1/4" - G3/8".

The connectors on these pages are also made without valve (OV).

All connectors can also be delivered with coloured red and blue caps.

Order e.g. with valve no. SLK 316
Without valve order no. SLK 316OV

Order e.g. valve no. SLK 316R = red cap

