

DYROS 80

Brass connectors with 13 mm passage capacity for water, grease, air, oil etc.

- developed specifically for coolants in plastic tools

- Today Dyros 80 can be found everywhere:
- on plastic moulds
 - on compressed-air plants
 - on oxygen and gas cylinders
 - in operating rooms
 - and in numerous other places

In short, Dyros can be found wherever small dimensions, reliability and safety are a must. All connectors have built-in valves that are perfectly tight even at very low pressure.

A locking device is automatically released upon engagement, so that the connector can be operated by one hand.

Safety connectors with hose fitting		1/2" (12,7°)	3/4" (19°)				
Straight	60 32	Art. No. SLK 818	Art. No. SLK 819				
	82 31 32	Art. No. SVK 818/90	Art. No. SVK 819/90				
	82 31 32	Art. No. SVK 818/45	Art. No. SVK 819/45				

Safety connectors with external thread		BSP1/2"	BSP 3/4"	M24x1.5			
Straight	65 L HEX	Art. No. SLKUR 812 (L = 12) (HEX = 30)	Art. No. SLKUR 834 (L = 16) (HEX = 30)	Art. No. SLKUM 824 (L = 16) (HEX = 30)			
	82 31 HEX L	Art. No. SVKUR 812/90 (L = 12) (HEX = 22)	Art. No. SVKUR 834/90 (L = 16) (HEX = 27)	Art. No. SVKUM 824/90 (L = 16) (HEX = 27)			
	82 31 HEX L	Art. No. SVKUR 812/45 (L = 12) (HEX = 22)	Art. No. SVKUR 834/45 (L = 16) (HEX = 27)	Art. No. SVKUM 824/45 (L = 16) (HEX = 27)			

Safety adaptor connector with nipple fitting		serie:	40	90
60 31			Art. No. SLK 800/400	Art. No. SLK 800/900

Dyros products are unimpeachable quality - down to the smallest detail

The Thread BSP corresponds to G1/2" - G3/4"

The connectors on these pages are also made without valve (OV).

All connectors can also be delivered with coloured red and blue caps.

Order e.g. with valve no. SLK 819
Without valve order no. SLK 819OV

Order e.g. valve no. SLK 819R = red cap

